

IPF COLLECTION _ FREE TIME**wood flooring for outdoor in unfinished solid wood****Size / Wood:**

solid	DOGA 19/90	19x90x930/1830 mm_ installation with screws or fasteners	Ipé Tabebuia
solid	DOGA 21/145	21x145x930/1830 mm_ installation with screws	Ipé Tabebuia

Grades (details available in our Technical Area):

Comfort

Finish:

unfinished, to finish with "FREE TIME"oil

Ordinary maintenance:

We suggest to clean the wood flooring every month or 6 months with specific cleaners, according to the usage or when needed.

For further information or the complete maintenance program, please contact our technical department.

First application of oil:

Apply Free Time oil with a paint brush; avoid the application in the warmest hours of the day. The surface has to be perfectly dry.

Usage:

outdoor: residential, commercial/high traffic

Emissions:

All IPF floors are free from harmful emissions in compliance with CE standards

Fire reaction class:

Dfl-s1

Accessories for installation:

installation with screws

• Joist	Ipé Tabebuia	38x38x950/2150 mm	ml. x m ²	3,00
• Screws for DOGA	Steel	4x50 mm	pz. x m ²	60

installation with fasteners

• Joist	Ipé Tabebuia	38x38x950/2150 mm	ml. x m ²	3,00
• Screws for fasteners	Steel	4,5x20 mm	pz. x m ²	60
• Fasteners	Steel	38x42 mm	pz. x m ²	30

IPF reserves the right to change technical specifications, size and appearance of the proposed products, as well as the right to replace or discontinue certain items without prior notice. This does not give the purchaser the right to demand cancelled or modified items. For further information and technical details, please contact our sales department.